



Technical Data Sheet

Ezycaulk

Butyl Rubber Sealant

Description

Z Bond® Ezycaulk is a one part, synthetic rubber mastic sealant that has been formulated to remain permanently flexible in use.

Features

- Interior and exterior applications.
- Will provide a dust and weather seal to joints
- Will accommodate movement of 2% to 4%.
- Will not cause corrosion when used in conjunction with coated steel, galvanised iron, Zinalume® and other similar products.

Z Bond® Ezycaulk forms a “tough skin” which allows subsequent painting.

Recommended Uses

- Suitable for use on concrete, brick, cement sheet, and other masonry products, and on timber, aluminium and steel.
- Cool room panel joint sealing

Other common uses include automotive windscreen rubber gaskets and caravans.

Application Instructions

Surface Preparation

Surfaces must be clean, dry and free from oil, dust and other foreign materials

Application

1. Cut a nozzle to extrude the required bead size.
2. Cut the end from the nipple on the cartridge.
3. Screw on the prepared nozzle.
4. Use a standard 300ml cartridge hand or air gun to apply the sealer.
5. Apply the sealant to one side of the joint and bring the other surface into contact while the sealant is still wet.
6. Use mechanical fastening (screws, rivets etc.) to secure the joint.

Curing

Z Bond® Ezycaulk will skin over in 8 -15 minutes.

Limitations

Z Bond® Ezycaulk is **NOT** suitable for use in the following applications:-

- When you need a sealant to fully cure.
- This product is not an adhesive



Properties

SYSTEM PROPERTIES

Property	Mean Result Achieved
Tack @ 48 Hours	Nil
Sag or Slump	Nil

TEMPERATURE

	Minimum	Maximum
Application Temperature	+5°C	+35°C
Service Temperature	0°C	+55°C

Storage & Shelf Life

Store in a cool, dry place, out of direct sunlight. For maximum shelf life, store between 5° and 20°C.

Shelf life is up to 12 months when stored in original, unopened containers, under the above conditions.

Health & Safety

Please refer to the Material Safety Data Sheet which is available on request.

Packaging

Z Bond® Ezycaulk is supplied in 300ml polyethylene cartridges, 15 to a carton.

Product Details

Item Number	Size	Colour	Pack Quantity
309310	300ml	White	15 cartridges

