

### Description

**AW 901 Cleaner/Thinner** is a specifically formulated solvent blend that is ideally suited for cleaning off dried water based and solvent based adhesives, such as spillage and adhesive oversprays.

**AW 901 Cleaner/Thinner** is especially suitable for use with solvent based contact adhesives.

### Recommended Uses

- As a thinner for AW brush, roller, and scraper grade contact adhesives.
- For thinning spray contacts but is generally not required.
- For cleaning metal tools.
- Cleaning/Soaking metal spray gun parts and scrapers.



### Application Instructions

**AW 901** should be applied directly to dried adhesive to soften the film, followed by removal by gradually scraping or wiping the adhesive away.

Spills and overspray can be removed by wiping with a rag soaked in **AW 901**

As a Thinner, **AW 901** is formulated to thin AW solvent base contact adhesives 101, 101R, 2700/1

### Limitations

- Do not use on expanded polystyrene foam.
- Do not use on PVC, ABS, Styrene or similar plastic surfaces.
- Do not use to thin adhesives used for polystyrene foam.

### Properties

<b>Appearance</b>	Water Clear
<b>Base</b>	Blend of hydrocarbon and Ketone solvents
<b>Shelf Life</b>	Approximately 1 year in original sealed container at 20°C
<b>Flash Point</b>	Less than 0°C

### Storage & Shelf Life

Store in a cool, dry place, out of direct sunlight and away from all sources of ignition. Storage areas must be well ventilated and comply with Local, State and Federal regulations. For maximum shelf life, store between 5° and 20°C.

Shelf life is up to 12 months when stored in original, unopened containers, under the above conditions.

### Health & Safety

Please refer to the Material Safety Data Sheet which is available on request. The solvents contained within this product are Highly Flammable.

### Product Details

Item Number	Size	Pack Quantity
503290	20 Litre	

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF  
BOSTIK AUSTRALIA PTY LTD**

Head Office      Bostik Australia Pty Ltd, 51-71 High Street, Thomastown Vic 3074  
A.B.N. 79 003 893 838  
Phone: (03) 9279 9333      Fax: (03) 9261 4744  
Phone Industrial:      Toll free 1300 560 799



Product:      AW 901  
Issue Date:      September 2014  
Issue No.:      4  
Author:      David V Stuart  
Division:      Industrial Adhesives  
Total Pages:      2