



---

# ADVABOND 95

---

## Description

ADVABOND 95 is a versatile, high solids adhesive that has many applications. ADVABOND 95 has high initial tack, good grab and a very fast set speed.

It may be used for:

- closure of packets on high speed equipment where laminated or wax art board is used.
- laminating supported and unsupported PVC (polyvinyl chloride) films to porous substrates such as hardboard, plywood, etc.
- head bands and casing-in
- bonding of certain films, foil and plain and coated papers.

## Typical Properties

Appearance	White creamy liquid
Viscosity	5,000 – 7,000 cps
Total Solids Content	53 - 57 %
Specific Gravity	1.06 g/ml

## Application Information

ADVABOND 95 is designed to be applied by nozzle, wheel or roller and runs on most types of equipment.

## Limitations

Check machine and material compatibility prior to commercial use.

## Cleaning

After use, brushes, rollers, glue baths and other equipment should be washed with warm water before the adhesive dries out.

## Storage

Product should be stored in the original container out of direct sunlight between 5°C and 30°C and protected from freezing. Rotate stock using oldest batches first. Close containers air tight after use. For best performance use product within 12 months.

## Safety & Disposal

This material is non-hazardous. Refer to the Material Safety Data Sheet (MSDS) for further information. This product meets the criteria for FDA CFR21 175. 105 "INDIRECT FOOD ADDITIVES: ADHESIVES".

All information is based on results gained from experience and tests therefore believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as the required performance, production techniques and substrates used can vary significantly. Therefore it is imperative that a full evaluation is undertaken to confirm the suitability of the product before commercial production.