



ADVABOND ML

Description

ADVABOND ML is a specially designed and unique product for bonding difficult substrates such as melamine, particularly in cabinet making applications.

Typical Properties

Appearance	White creamy liquid
Viscosity	6,500-7,500 cPs
Total Solids Content	55-57 %
Specific Gravity	1.07 g/ml

Application Information

Ensure substrates are free from oils dirt or grease.

ADVABOND ML is primarily designed to be used by squeeze bottle or brush. Apply enough adhesive to ensure the glue line is fully covered and wet-out when surfaces are pressed together.

Dilution is not recommended.

Limitations

It should not be used for exterior or load bearing applications.

Cleaning

Clean up adhesive while wet with warm water.

Storage

Product should be stored in the original container out of direct sunlight between 5°C and 30°C and be protected from freezing. Rotate stock using oldest batches first. Close containers air tight after use. For best performance use product within 12 months.

Safety & Disposal

This material is non-hazardous. Refer to the Material Safety Data Sheet (MSDS) for further information.

All information is based on results gained from experience and tests therefore believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as the required performance, production techniques and substrates used can vary significantly. Therefore it is imperative that a full evaluation is undertaken to confirm the suitability of the product before commercial production.