





Cost efficient

Less material needed to provide optimal protection



Time savings

Pad is created at high speed with minimal reloading necessary



Ergonomic

Easy to handle packs of paper, several modes including EDS

The **high speed solution** for light **cushioning** and **void fill**





The PadPak LC is the fastest paper cushioning solution on the market. The high output allows a maximum box throughput. The converter forms single layer paper into pads which can be used to protect products during shipment. The individual fanfolded packs of paper, with gluing strip, ensure the converter is easy to load and runs at high speed. The paper pad can be used for cushioning, fixating or wrapping.



Go Green

Our company works with FSC certified suppliers. Paper is climate neutral, recyclable and also a renewable source.

Specifications of the system

Converter

 Dimensions:83x110x127-166 cm horizontal position

 Dimensions:83x76x149-188 cm vertical position

Weight: 100 kgPower: 830 WattVoltage: 100 - 230 Volt



Paper

Base weight: 70 gr/m², 90 gr/m²
Pack length: 360 m, 300 m

· Paper width: 76 cm

• Pack weight: 19.2 kg, 20.6 kg

Our Added Value







Packaging Engineering

Ranpak analyses and reports on your current packaging solution. The drop test shows exactly how much shock is transmitted to your products through the packaging. Ranpak then suggests alternatives how to improve protection or save costs.

Integrated Applications

The Ranpak Added Value department can design structures, frames and other innovative solutions to integrate the packaging converter anywhere around, above or under a packing area.

Packaging Training

Training from our packaging experts will help your packers to use up to 20% less packing material, without compromising the quality of the packaging.

Successful in these industries

E-commerce	Medical	Electronics	Retail	Technical instruments
Tools	Logistics	Computers	Decoratives	Cosmetics

Your Ranpak Distributor



*Ask your distributor for the details of this promotion.