

# 3M™ Scotch-Weld™ Hot Melt Adhesives

Promotion: 1 February – 1 April 2015



## Speed & productivity

at the touch of your finger

### SPECIAL OFFER

Buy any 5 cartons of 3M™ Scotch-Weld™ Hot Melt Adhesives\* and receive for FREE a 3M™ TC-Q or LT-Q Adhesive Applicator worth over \$280!<sup>RRP^</sup>

\*3738, 3762, 3764, 3762LM, 3792LM

Easy to use,  
fast bonding system

- Improve productivity
- Minimise waste
- Available in hot and low melt options



The 3M logo is displayed in red.



## Hot melt systems for speed and productivity

3M Scotch-Weld Hot Melt adhesives are solid resins that become fluid when heated and quickly wet the bonding surface. They cool, harden and reach bond strength in seconds allowing you to move assemblies immediately to keep production flowing. This helps eliminate clamps, fixtures and drying; saving time, energy and space.

	Product	Key Features	Colour	Applicator	Stick Type	Stick Size (mm)	Qty Sticks per Kg (approx)	Coverage <sup>1*</sup> (metres per stick)	Bonding Range <sup>2</sup> (sec)	Temperature resistance <sup>3</sup> (°C)	Shear Strength (kPa)
Low Melt	3762LM	Low melt version of 3762. Fast setting for packaging applications	Light Amber	LTQ	Quadrack	15x200	33	7.4	25	54	3,310
	3792LM	General purpose for heat sensitive substrates, e.g POS Displays	Clear	LTQ	Quadrack	15x200	33	7.4	40	60	2,410
Hot Melt	3738	High delivery rate and long bonding range	Tan	TCQ	Quadrack	15x200	33	7.4	50	54	2,590
	3762	Excellent hot-tack for fast setting applications	Tan	TCQ	Quadrack	15x200	33	7.4	35	54	3,760
	3764	Flexible at low temperatures. Excellent polyolefin plastic bonding.	Clear	TCQ	Quadrack	15x200	33	7.4	40	60	2,700

1. Based on a 3.175mm wide semicircular bead. 2. Bonding Range: time available to apply the 2nd substrate when a 3mm semicircular bead is applied to the 1st surface. Test results based on, Douglas Fir to Douglas Fir. Actual results may vary depending on the substrates being bonded and amount of adhesive applied. 3. Heat Resistance - Temperature at which adhesive fails, using SAFT Shear Adhesion Failure Test with birch plywood, 1 inch overlap, 100 grams used, temperature start at 90F and ramped 10F every 10 min. until complete failure.

## Buy any 5, 5kg cartons of adhesive and receive an applicator for FREE!

Adhesive	SKU	Size (kg)	Sticks per Carton (approx.)	FREE Applicator
3738 TCQ 5kg	62373891324	5	165	TC-Q Adhesive Applicator 62970099495
3762 TCQ 5kg	62376291324	5	165	
3764 TCQ 5kg	62376491320	5	165	
3762 LMQ 5kg	62372091322	5	165	LT-Q Adhesive Applicator 62928199363
3792 LMQ 5kg	62376091328	5	165	

Terms and Conditions: Offer valid only during the promotional period. Offer extends to 3M™ Scotch-Weld™ Hot Melt 3738, 3762, 3764, 3762LM & 3792LM adhesives. Offer not valid in conjunction with any special pricing. Offer valid dependent on stock availability during promotional period. Forward orders will not be accepted outside of promotional period. ^Recommended Retail Price.



**3M Australia Pty Ltd**  
**Industrial Adhesives & Tapes Division**  
 Bldg A, 1 Rivett Road  
 North Ryde NSW 2113  
 Australia  
 Phone: 136 136  
[www.3m.com/adhesives](http://www.3m.com/adhesives)

3M and Scotch-Weld are trademarks of 3M Company.  
 Please recycle. Printed in Australia.  
 © 3M 2015. All rights reserved.