

Tork Premium Multipurpose Cloth 530 Folded



benefit

- Strong, thick and bulky
- Allows hard scrubbing and though solvents without falling apart
- Textured surface makes it easy to remove grease and stubborn spots
- Protects hands both from heat when handling hot plates and pans, and from being cut by metal scraps
- Heat resistant
- Safe food handling is assured by the ISEGA certificate.





product properties

article	system	Unfolded Length	Unfolded Width	Folded Length	Folded Width	Ply	Print	Colour
530178	W4 - Top pak system, W4 - Top pak system	42.8 cm	38.5 cm	10.8 cm	38.5 cm	1	no	White



Tork Premium Multipurpose Cloth 530 Folded

shipping data

consumer unit

EAN	7322540057607		
pieces	100		
material	Plastic		
height	220 mm		
width	107 mm		
length	380 mm		
volume	8.9 dm3		
net weight	1318 g		
gross weight	1345 g		

pallet

EAN	7322540275995		
pieces	12500		
consumer units	125		
height	1358 mm		
width	1000 mm		
length	1200 mm		
volume	1.3 dm3		
net weight	164.75 kg		
gross weight	186.85 kg		

transport unit

EAN	7322540057614		
pieces	500		
consumer units	5		
material	Carton		
height	239 mm		
width	396 mm		
length	555 mm		
volume	52.5 dm3		
net weight	6.59 kg		
gross weight	7.47 kg		

Tork Premium Multipurpose Cloth 530 Folded

environmental

Content

Chemical pulp, Polypropene, Polyester, Chemicals

Material

Chemical pulp Chemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.ECF is used in this product.

PolypropenePolypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength. PolyesterPolyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength. Chemicals Both functional and process chemicals are used. The functional chemical used wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.